
Safety Data Sheet



Product identifier	
Product Name	 Pennington Seed Professional Turf Fertilizer
Product Code	FertCa
Product Description	Variable colored granules.
Relevant identified uses	of the substance or mixture and uses advised against
Recommended use	Fertilizer for lawns.
Restrictions on use	 Keep out of reach of children and domestic animals. Avoid breathing dust. Avoid contact with eyes, skin and clothing.
Details of the supplier o	f the safety data sheet
Manufacturer	 Pennington Seed, Inc. 9675 S. 60th Street Franklin, WI 53132 United States

Telephone (General) • 1-414-394-3590 - 8:30am - 5:00pm M-F

Emergency telephone number

Manufacturer (Transportation) • 1-800-424-9300 - CHEMTREC - for transportation and non-transportation emergencies Manufacturer (Transportation) • 1-703-527-3887 - CHEMTREC - Outside the US collect calls accepted

Section 2: Hazard Identification

United States (US) According to: OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

OSHA HCS 2012

Carcinogenicity 1A

Label elements OSHA HCS 2012



DANGER

Hazard statements • May cause cancer.

Precautionary statements

Prevention •

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.

PENNINGTON

- **Response** IF exposed or concerned: Get medical advice/attention.
- Storage/Disposal •

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations. Store locked up.

Other hazards

OSHA HCS 2012

Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Section 3 - Composition/Information on Ingredients

Substances

Material does not meet the criteria of a substance according to United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

Mixtures

Composition		
Chemical Name	Identifiers	%
Limestone	CAS:1317-65-3	> 10%
Silica, crystalline - quartz	CAS:14808-60-7	> 0.1%
Fertilizer ingredients	NDA	> 89%

Section 4: First-Aid Measures

Description of first aid measures

Inhalation

IF INHALED: If breathing is difficult, remove person to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms occur.

Skin IF ON SKIN: Wash skin with soap and water. If irritation develops and persists, get medical attention.

Eye

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion First aid is not expected to be necessary if material is used under ordinary conditions and as recommended.

Most important symptoms and effects, both acute and delayed

• May cause cancer. Refer to Section 11 - Toxicological Information.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

• Treat symptomatically and supportively.

Section 5: Fire-Fighting Measures

Extinguishing media

Suitable Extinguishing Media	1.	SMALL FIRES: Dry chemical, CO2, water spray or regular foam. LARGE FIRE: Water spray, fog or regular foam.
Unsuitable Extinguishing Media	•	Avoid heavy hose streams.
Special hazards arising	frc	om the substance or mixture
Unusual Fire and Explosion Hazards	•	None known.
Hazardous Combustion Products	•	Non-combustible, substance itself does not burn but may decompose upon heating to produce corrosive and/or toxic fumes.
Advice for firefighters		
	•	Wear positive pressure self-contained breathing apparatus (SCBA).

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Avoid contact with skin, eyes, and clothing. Wear appropriate personal protective equipment, avoid direct contact. Ventilate enclosed areas. Avoid dust formation and breathing dust.
Emergency Procedures	No emergency procedures are expected to be necessary if material is used under ordinary conditions as recommended.
Environmental precaution	IS
	No data available
Mothodo and motorial for	containment and cleaning up

Methods and material for containment and cleaning up

Containment/Clean-up	 Sweep or scoop up spills, dispose of any unusable material in approved landfill.
Measures	Use appropriate Personal Protective Equipment (PPE).
Measures	

Section 7 - Handling and Storage

Precautions for safe handling

Handling

Avoid contact with skin, eyes, and clothing. Avoid breathing dust. To minimize dust generation and accumulation, spills should be cleaned up and dust accumulationsshould be removed promptly. Wash thoroughly with soap and water after handling.

Conditions for safe storage, including any incompatibilities

Storage

Store in a cool/low-temperature, well-ventilated, dry place. Keep out of reach of children. Keep container tightly closed. Avoid humid, wet or moist conditions. Keep away from incompatible materials such asreducing agents. Do not blend or store in contact with ammonium nitrate. Ventilate enclosed areas. Store locked up.

Incompatible Materials or Ignition Sources

May be corrosive to mild steel. slightly corrosive to aluminum, zinc, or copper and non -corrosive to glass, 304 or 316 stainless steel. May be reactive with halogens and slightly reactive with oxidizing agents, reducing agents, acids, alkalis, moisture.

Section 8 - Exposure Controls/Personal Protection

Control parameters

	Exposure Limits/Guidelines			
	Result	ACGIH	NIOSH	OSHA
Silica, crystalline - quartz (14808-60-7)	TWAs	0.025 mg/m3 TWA (respirable fraction)	0.05 mg/m3 TWA (respirable dust)	0.05 mg/m3 TWA (respirable dust)
Limestone (1317-65-3)	TWAs	Not established	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)

Exposure Limits Supplemental

OSHA

•Silica, crystalline - quartz (14808-60-7): Mineral Dusts: ((30)/(%SiO2 + 2) mg/m3 TWA, total dust; (250)/(%SiO2 + 5) mppcf TWA, respirable fraction; (10)/(%SiO2 + 2) mg/m3 TWA, respirable fraction)

ACGIH

•Silica, crystalline - quartz (14808-60-7): TLV Basis - Critical Effects: (lung cancer; pulmonary fibrosis)

Exposure controls

Engineering Measures/Controls

Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values.

Pe

Personal Protective Equipmen Pictograms	• • • • •
Respiratory	 If airborne dust is present or in case of inadequate ventilation, use appropriate respiratory protection. Use of half/full face air purifying or N95 dust mask is recommended.
Eye/Face	Wear safety glasses.
Hands	Wear appropriate gloves.
Skin/Body	 If prolonged exposure is anticipated, it is recommended for handlers to wear appropriate clothing to prevent skin contact. Use full body suit such as Tyvek or Tychem suit is recommended.
General Industrial Hygiene Considerations	 Handle in accordance with good industrial hygiene and safety practice.
Environmental Exposure Controls	No data available

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description			
Physical Form	Solid	Appearance/Description	Variable colored granules.
Color	Varies	Odor	Varies
Odor Threshold	No data available		
General Properties		-	
Boiling Point	No data available	Melting Point/Freezing Point	No data available
Decomposition Temperature	No data available	рН	Not relevant
Specific Gravity/Relative Density	No data available	Bulk Density	45 to 80 lb(s)/ft ³
Water Solubility	No data available	Viscosity	Not relevant
Volatility	-		
Vapor Pressure	No data available	Vapor Density	No data available
Evaporation Rate	No data available		
Flammability			
Flash Point	Not relevant	UEL	No data available
LEL	No data available	Flame Duration	No data available
Flammability (solid, gas)	No data available		
Environmental			
Octanol/Water Partition coefficient	No data available		

Section 10: Stability and Reactivity

Reactivity

· Non-reactive under normal handling and storage conditions.

Chemical stability

Stable

Possibility of hazardous reactions

• Hazardous polymerization will not occur.

Conditions to avoid

Extreme heat, high humidity or moisture. Avoid contact with moisture. If Urea is present, slow hydrolysis may produce acids corrosive to metals.

Incompatible materials

Material may be incompatible with halogens, oxidizing agents, reducing agents, acids, alkalis, moisture, potassium chlorate, potassium nitrate, sodium nitrate, sodium hypochlorite, metal chlorates, strong bases. If Urea is present may be corrosive to mild steel and slightly corrosive to aluminum, zinc, or copper.

Hazardous decomposition products

May release ammonia, oxides of sulfur, oxides of nitrogen, and oxides of carbon. Flammable/toxic gases will form at elevated temperatures by thermal decomposition.

Section 11 - Toxicological Information

Information on toxicological effects

GHS Properties	Classification OSHA HCS 2012 • Acute Toxicity - Dermal - Classification criteria not met; Acute Toxicity - Inhalation - Classification criteria not met; Acute Toxicity - Oral - Classification criteria not met		
Acute toxicity			
Skin corrosion/Irritation	OSHA HCS 2012 • Classification criteria not met		
Serious eye damage/Irritation	OSHA HCS 2012 • Classification criteria not met		
Skin sensitization	OSHA HCS 2012 • Classification criteria not met		
Respiratory sensitization	OSHA HCS 2012 • Classification criteria not met		
Aspiration Hazard	OSHA HCS 2012 • Classification criteria not met		
Carcinogenicity	OSHA HCS 2012 • Carcinogenicity 1A		
Germ Cell Mutagenicity	OSHA HCS 2012 • Not classified - data lacking		
Toxicity for Reproduction	OSHA HCS 2012 • Classification criteria not met		
STOT-SE	OSHA HCS 2012 • Classification criteria not met		
STOT-RE	OSHA HCS 2012 • Classification criteria not met		

1		- 4 !	
IN	na	iati	on

Acute (Immediate)	• Exposure to dust may cause mild respiratory irritation. Acute Silicosis can occur with exposures to very high concentrations of respirable crystalline silica over a very short time period, sometimes as short as a few months. The symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss.
Chronic (Delayed)	 Repeated or prolonged inhalation of dust may cause respiratory irritation. Repeated and prolonged exposure to crystalline silica containing materials may cause irritation and/or lung damage silicosis, fibrosis, inflammation, cancer.
Skin	
Acute (Immediate)	 Exposure to dust may cause mechanical irritation.
Chronic (Delayed)	No data available.
Eye	
Acute (Immediate)	 Exposure to dust may cause mechanical irritation.
Chronic (Delayed)	No data available
Ingestion	
Acute (Immediate)	 Under normal conditions of use, no health effects are expected.
Chronic (Delayed)	No data available
Other	
Chronic (Delayed)	No data available.
Carcinogenic Effects	 Crystalline silica (quartz) inhaled from occupational sources is classified as carcinogenic to humans.

Section 12 - Ecological Information

Toxicity

Section 13 - Disposal Considerations

Waste treatment methods

- Product waste
 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.
 Packaging waste
 Dispose of content and/or container in accordance with local, regional, national, and/or
 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	UN number	UN proper shipping name	Transport hazard class (es)	Packing group	Environmental hazards
DOT	NDA	Not Regulated	NDA	NDA	NDA
IMO/IMDG	NDA	Not Regulated	NDA	NDA	NDA
IATA/ICAO	NDA	Not Regulated	NDA	NDA	NDA

Special precautions for user • None specified.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Other information	•	No data available
IMO/IMDG	•	No data available

IATA/ICAO . No data available

Key to abbreviations

= N/A = Not applicable.

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture SARA Hazard Classifications • Chronic

Inventory						
Component	CAS	TSCA				
Limestone	1317-65-3	Yes				

Silica, crystalline - quartz	14808-60-7	Yes		
Section 16 - Other Information				
Revision Date	•	06/October/2016		

Rottolon Bato	• 00/000000/2010
Last Revision Date	• 06/October/2016
Preparation Date	• 06/October/2016
Disclaimer/Statement of Liability	• The information a

The information and statements herein are believed to be reliable but are not to be construed as a warranty or representation for which we assume legal responsibility. Users should undertake sufficient verification and testing to determine the suitability for their own particular purpose of any information or products referred to herein. NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE.